

10598859

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 September 2005 (29.09.2005)


PCT

(10) International Publication Number
WO 2005/089580 A1

- (51) International Patent Classification⁷: **A43B 17/02**, B29D 31/518
- (21) International Application Number: PCT/IB2005/000656
- (22) International Filing Date: 15 March 2005 (15.03.2005)
- (25) Filing Language: Italian
- (26) Publication Language: English
- (30) Priority Data: VI2004A000052 15 March 2004 (15.03.2004) IT
- (71) Applicant (for all designated States except US): **TECHNOGEL ITALIA S.R.L.** [IT/IT]; Via Vittorio Emanuele, 141, I-36050 Pozzolunc (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **LOSIO, Massimo** [IT/IT]; Via Forestuzzo, 2, I-31011 Asolo (IT). **BRAGHIN, Irene** [IT/IT]; Via dei Salici, 12, I-21059 Viggiu' (IT).
- (74) Agent: **MAROSCIA, Antonio**; Maroscia & Associati SRL, Contrà S. Caterina, 29, I-36100 Vicenza (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GI, GM, GR, GU, HK, HN, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: COMPOSITE FOOTWEAR INSOLE, AND METHOD OF MANUFACTURING SAME



(57) Abstract: A composite footwear insole has a front portion (2) designed to interact with the foot at the metatarsal region and at least partly at the plantar arch, and a rear portion (3) designed to interact with the heel. The rear portion (3) has at least one layer (4) of gel material whose size is at least substantially equal to that of the rear portion (3) to uniformly support the heel and absorb stresses acting thereon.

WO 2005/089580 A1



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

COMPOSITE INSOLE FOR FOOTWEAR AND MANUFACTURING METHOD

Field of the invention

5

This invention generally finds application in the field of footwear and particularly relates to a composite insole as defined in the preamble of claim 1, and to a method of manufacturing same.

10

Prior art

The heel is known to be the portion of the foot that is most subjected to shocks and impulsive stresses during walking. For this reason, in many footwear and insole products shock absorbing members are provided at the heel region.

Particularly, EP-A-1166671, WO-A-0024283, WO-A-9831249, US-A-2002092203, US-A-5718063 disclose insoles having a polymeric base material and at least one cavity or opening in which one or more gel inserts are received. Generally, at least one gel insert is placed in a rear portion of the insole at the user's heel to absorb shocks from the ground.

A drawback of such arrangements is that the insert has a small size and causes an uneven distribution of mechanical properties in the rear portion and the insole, thereby affecting comfort for the user. Particularly, transition portions having different stiffness properties are provided between the base material and the gel material. These transition

portions may be felt by the wearer and may be particularly uncomfortable as they are placed in the rear portion of the insole, which is subjected to frequent and relatively high stresses.

5

US-A-2002166259 and FR-A-2808427 disclose respective insoles having a layer of gel material with an upper surface extending substantially all over the plant of the user's foot. A cover layer is further provided, for
10 wholly covering at least the upper surface of the gel layer, in such a manner as to prevent direct contact therewith.

A disadvantage of such arrangements lies in that the
15 cover layer may limit the shock absorbing capacity of the gel layer, thereby affecting the comfort level during walking. Additionally, the arrangement disclosed in US-A-2002166259 provides local portions having different stiffnesses, which can cause inconvenient
20 discontinuities of the pressure felt by the foot and affect the overall comfort.

EP-A-0774219 discloses a footwear insole having a base body made of polymeric foam and a cushion filled with
25 gel positioned on the upper surface of the insole to interact with the user's foot. The insole further has a cavity at the heel portion, which is designed to receive a member for absorption of impulsive stresses on the heel.

30

A disadvantage of this arrangement consists in that the interaction between the gel cushion and the base body and the interaction between the gel contained in the

cushion and the walls thereof may affect the shock absorption and deformation capacities of the gel, thereby reducing the stress absorption effect.

5 Summary of the invention

A primary object of this invention is to obviate the above drawbacks, by providing a composite footwear insole having high comfort properties.

10

A particular object is to provide an insole which can uniformly distribute stress over the foot and particularly over areas subjected to higher pressure, such as the heel and the metatarsal regions.

15

A further object of the invention is to provide an insole which has a continuous surface in contact with the foot at the areas subjected to greater stress, which has no discontinuity in stiffness or other
20 mechanical properties.

Yet another particular object is to provide an insole which allows transpiration at the foot areas that are more prone to sweating.

25

These objects, as well as other objects that will be more apparent hereafter, are fulfilled, according to claim 1, by a composite footwear insole having a front portion for interacting with the foot at the metatarsal
30 region and at least partly at the plantar arch, and a rear portion for interacting with the heel, characterized in that the rear portion has at least one top layer of gel material whose plan size is at least

substantially equal to that of the rear portion to uniformly support the heel and absorb stresses acting thereon.

5 Thanks to this particular arrangement, a particularly comfortable insole may be provided, which can uniformly distribute stresses on the foot and particularly on the heel.

10 Brief description of the drawings

Further characteristics and advantages of the invention will be more apparent from the detailed description of a few preferred, non-exclusive embodiments of an insole according to the invention, which are described as a non-limiting example with the help of the annexed drawings, in which:

FIG. 1 is a perspective view of a first insole according to the invention;
20 FIG. 2 is a perspective view of a second insole according to the invention;
FIG. 3 is a perspective view of a third insole according to the invention;
FIG. 4 is a perspective view of a fourth insole
25 according to the invention;

Detailed description of a preferred embodiment

Particularly referring to the above figures, a composite insole according to the invention, designed for various footwear types, and generally designated by numeral 1, will be described.

The insole 1 has a front portion 2 for interacting with the foot at the metatarsal region and at least partly at the plantar arch, and a rear portion 3 for interacting with the heel.

5

A peculiar feature of the invention is that the rear portion 3 has a gel layer 4 whose plan size is substantially equal to that of the rear portion 3 itself. Thus, the heel may be evenly supported and stresses thereon may be effectively absorbed.

10

The gel layer 4 may have an upper surface 5 for interacting with the heel, which is substantially continuous, with no surface discontinuity, to further increase comfort. Furthermore, the gel layer 4 may be made either of one piece, from one gel material, or of multiple superimposed layers of different gel materials. For example, two gel materials having different stiffnesses and/or densities may be used. Gel materials may be of various kinds, and preferably of the polyurethane type.

15

20

In certain embodiments, the rear portion 3 may be wholly made of gel material, as shown in FIG. 1 and FIG. 3. In this case, the gel layer 4 extends through the whole thickness of the rear portion 3, which may be connected to the front portion 2 by a continuous junction 6.

25

In other embodiments, as shown in FIG. 2 and FIG. 4, the rear portion 3 may comprise a support base 7 made of a semi-rigid, natural or synthetic material, such as a polymeric foam, which lies under the gel layer 4.

30

Here, the support base 7 may only extend across the rear portion 3 or also across the front portion 2.

Both in case that the gel layer 4 extends through the whole thickness of the rear portion 3, and when a support base 7 is provided under the gel layer 4, the latter may be joined to the front portion 2 by a substantially continuous connecting portion 8, thereby providing a transition between the upper surface 5 of the rear portion 3 and the upper surface 9 of the front portion 2, which is substantially free of discontinuities and inconvenient steps.

The gel layer 4 may be finished at least on the upper surface 5 with a varnish which is capable of reducing tackiness between the rear portion 3 and the heel, to prevent the unpleasant sensation of partial tackiness between the heel and the upper surface 5.

Suitably, the gel layer 4 may have a raised peripheral edge (not shown in the drawings) to substantially conform to the heel anatomy and promote retention thereof during walking. Also, the rear portion 3 may have a one-piece appendix (not shown) which extends toward the plantar arch of the foot. Both this one-piece appendix and the raised edge are well-known arrangements to improve the anatomic fit of the insole 1 as well as comfort for the user.

The front portion 2 may comprise at least one layer of transpiring material (not shown in the drawings), which may be selected from the group of leathers, fibers, natural and/or synthetic fabrics. Furthermore, the

support base 7 may not only extend at the rear portion 3 but also under the transpiring layer, therefore at the front portion 2.

- 5 As shown in the annexed FIG. 3 and FIG. 4, the front portion 2 may comprise an insert 10 of gel material, placed at the metatarsal region, to also absorb shocks between the foot and the ground in this area.
- 10 The above insole 1 is fabricated according with a method as described below. Particularly, the method comprises the steps of forming a front portion 2 designed to interact with the foot at the metatarsal region and at least partly at the plantar arch, and
- 15 forming a rear portion 3, integral with the front portion 2, and designed to interact with the heel. In more detail, the method comprises the step of forming a gel layer 4, by molding it in a special mold (not shown), substantially over the whole plan size of the
- 20 rear portion 3.

The gel layer 4 may be molded in various manners. According to a first embodiment, the gel layer 4 is co-molded with the front portion 2. Thus, the previously

25 preformed front portion 2 is placed in the mold, and the gel material is introduced thereafter. Therefore, the gel layer 4 forms the whole rear portion 3 and such molding process allows to connect the front portion 2 to the rear portion 2 by a continuous junction 6.

30

In a second embodiment, the gel layer 4 is co-molded with the front portion and a support base 7 made of a semi-rigid material. Here, the gel material is molded

over the support base 7 at the rear portion 3 and permanently bonds both with the support base 7 and the front portion 2.

- 5 In a third embodiment, the front portion 2 and the rear portion 3 are fabricated separately and are later joined by a substantially continuous connecting junction. Here, the rear portion 3 may be either only formed by the gel layer 4 or also comprise the support
10 base 7. Further, the front portion 2 may be joined to the rear portion by gluing, stitching or other similar methods.

Once the intermediate assembly composed of the front
15 portion 2 and the rear portion 3 has been fabricated according to one of the above embodiments, the gel layer 4 may be varnished at one upper surface 5 to reduce tackiness to the heel.

- 20 Alternatively, before fabricating the rear portion 3 in accordance with any of the above embodiments, the mold may be previously coated with a non-stick varnish, designed to cover an upper surface 5 of the gel layer 4 to reduce its tackiness to the heel.

25

From the above disclosure, the insole of the invention proves to fulfill the proposed objects and particularly provides a high comfort level, by effectively absorbing shocks caused by foot/ground contact.

30

The insole of the invention is susceptible of a number of changes and variants, within the inventive concept disclosed in the appended claims. All the details

thereof may be replaced by other technically equivalent parts, and the materials may vary depending on different needs, without departure from the scope of the invention.

5

While the insole has been described with particular reference to the accompanying figures, the numerals referred to in the disclosure and claims are only used for the sake of a better intelligibility of the
10 invention and shall not be intended to limit the claimed scope in any manner.

CLAIMS

1. A composite footwear insole having a front portion
(2) for interacting with the user's foot at the
5 metatarsal region and at least partly at the plantar
arch, and a rear portion (3) for interacting with the
foot over the heel region, characterized in that said
rear portion (3) has at least one layer (4) of gel
material whose plan size is at least substantially
10 equal to that of said rear portion (3) to uniformly
support the heel and absorb stresses acting thereon.

2. Insole as claimed in claim 1, characterized in that
said gel layer (4) is made of one piece and has a
15 substantially continuous upper surface (5), free of
surface discontinuities.

3. Insole as claimed in claim 2, characterized in that
said rear portion (3) is wholly made of gel material.

20

4. Insole as claimed in claim 2, characterized in that
said rear portion (3) comprises a support base (7) made
of a semi-rigid, natural or synthetic material,
underlying said gel layer (4).

25

5. Insole as claimed in claim 2, characterized in that
said gel layer (4) is finished at least on said upper
surface (5) with a varnish which is capable of reducing
tackiness between said rear portion (3) and the heel.

30

6. Insole as claimed in claim 2, characterized in that
said gel layer (4) has a raised peripheral edge (4) to
conform to the heel anatomy and favor retention thereof.

7. Insole as claimed in claim 1, characterized in that said front portion (2) comprises at least one layer of transpiring material.
- 5 8. Insole as claimed in claim 4, characterized in that said semi-rigid support base (7) continuously extends even at said front portion (2).
9. Insole as claimed in claims 7 and 8, characterized
10 in that said support base (7) extends under said transpiring layer at said front portion (2).
10. Insole as claimed in claim 2, characterized in that said gel layer (4) is joined to said front portion (2)
15 by a substantially continuous connecting portion (8).
11. Insole as claimed in claim 2, characterized in that said rear portion (3) has a one-piece appendage extending toward the plantar arch of the foot.
20
12. Insole as claimed in claim 2, characterized in that said front portion (2) comprises a gel insert (10) placed at the metatarsal region.
- 25 13. A method of manufacturing a footwear insole as claimed in one or more of the preceding claims, comprising the steps of forming a front portion (2) designed to interact with the foot at the metatarsal region and at least partly at the plantar arch, and
30 forming a rear portion (3), integral with the front portion (2), and designed to interact with the heel, characterized in that it comprises the step of forming a gel layer (4), and molding it in a special mold,

substantially over the whole plan size of said rear portion (3).

14. Method as claimed in claim 13, characterized in
5 that said gel layer (4) is co-molded with said front portion (2).

15. Method as claimed in claim 13, characterized in
that said gel layer (4) is co-molded with said front
10 portion (2) and a semi-rigid support base (7).

16. Method as claimed in claim 13, characterized in
that the front portion (2) and the rear portion (3) are
fabricated separately and are later joined by a
15 substantially continuous connecting junction.

17. Method as claimed in claim 13, characterized in
that said gel layer (4) is coated at an upper surface
(5) thereof with a varnish which is capable of reducing
20 its tackiness to the heel.

18. Method as claimed in claim 13, characterized in
that a non-stick varnish is previously applied on said
mold for coating an upper surface (5) of the gel layer
25 (4) to reduce its tackiness to the heel.

1/2




FIG.1




FIG.2

2/2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT B2005/000656

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A43B17/02 B29D31/518

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A43B B29D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 299 05 961 U1 (ZIMMERMANN, JUERGEN) 16 September 1999 (1999-09-16) the whole document	1-3,7, 13,14
X	US 3 724 106 A (MAGIDSON H,US) 3 April 1973 (1973-04-03)	1-3,10, 12
A	column 2, line 26 - line 28 column 6, line 63 - line 64; figures	13
X	US 6 532 689 B1 (JONES, JR. LESLIE O) 18 March 2003 (2003-03-18)	1-3
A	column 2, line 25 - line 37; figure 3 column 2, line 57 - line 63	13
X	WO 00/24283 A (VINDRIIS, SOEREN) 4 May 2000 (2000-05-04)	1-3,7
A	cited in the application claims 1,6; figures	13
	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

° Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

11 July 2005

Date of mailing of the international search report

15 AUG. 2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Schölvinck, T.S.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/B2005/000656

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2001/018466 A1 (GANSEN PETER ET AL) 30 August 2001 (2001-08-30) paragraphs [0001], [0004], [0005], [0009], [0012] - [0014] paragraph [0035] - paragraph [0038] -----	13-16
A	EP 0 511 570 A (BAYER AG) 4 November 1992 (1992-11-04) page 7, line 40 - line 48 page 8, line 45 - line 46 -----	5,13-18
A	US 2002/092203 A1 (HARDT JOHN C) 18 July 2002 (2002-07-18) cited in the application paragraph [0029] - paragraph [0035] paragraph [0049]; figures -----	1,2,13
A	EP 1 166 671 A (UVEX ARBEITSSCHUTZ GMBH) 2 January 2002 (2002-01-02) cited in the application the whole document -----	1-18
A	WO 98/31249 A (CHEONG, WILSON) 23 July 1998 (1998-07-23) cited in the application the whole document -----	1-18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/B2005/000656

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 29905961	U1	16-09-1999	NONE	
US 3724106	A	03-04-1973	AU 3505871 A CA 941608 A1 DE 2152710 A1 FR 2144186 A5 GB 1330193 A IT 941724 B	03-05-1973 12-02-1974 25-01-1973 09-02-1973 12-09-1973 10-03-1973
US 6532689	B1	18-03-2003	NONE	
WO 0024283	A	04-05-2000	DK 138298 A AT 236545 T AU 6189199 A DE 69906773 D1 DE 69906773 T2 WO 0024283 A1 EP 1124463 A1 US 6865823 B1	28-04-2000 15-04-2003 15-05-2000 15-05-2003 05-02-2004 04-05-2000 22-08-2001 15-03-2005
US 2001018466	A1	30-08-2001	DE 19957397 C1 CA 2327017 A1 EP 1103371 A2 JP 2001163991 A SG 102602 A1 TW 574098 B	19-07-2001 29-05-2001 30-05-2001 19-06-2001 26-03-2004 01-02-2004
EP 0511570	A	04-11-1992	DE 4114213 A1 AT 150041 T CA 2067463 A1 DE 59208154 D1 DK 511570 T3 EP 0511570 A1 ES 2099178 T3 FI 921917 A IE 921400 A1 JP 5186558 A NO 921549 A US 5362834 A	05-11-1992 15-03-1997 02-11-1992 17-04-1997 08-09-1997 04-11-1992 16-05-1997 02-11-1992 04-11-1992 27-07-1993 02-11-1992 08-11-1994
US 2002092203	A1	18-07-2002	WO 02056718 A1	25-07-2002
EP 1166671	A	02-01-2002	DE 20011334 U1 EP 1166671 A2	21-12-2000 02-01-2002
WO 9831249	A	23-07-1998	AU 757727 B2 AU 5183898 A AU 5543398 A WO 9831249 A1 US 6003250 A	06-03-2003 23-07-1998 07-08-1998 23-07-1998 21-12-1999